



PHANOTRONS



DIODES A GAZ

- Valves à vapeur de mercure
- Valves à gaz inerte (xénon)

RÉFÉRENCE	CATHODE		CARACTÉRISTIQUES (max.)			ACCESSOIRES		ÉQUIVALENCE U. S. A.
	Ef V	If A	E inv. crête V	Ia moy. A	Ia crête A	Connexion d'anode	Support	
● TH 5021 $\frac{B}{V}$ (a)	2,5	5	10.000	0,4	1,2	13305	16006 16019	866 866 A
● TH 5031 $\frac{B}{V}$ (a)	5	7,5	10.000	1,2	4,8	13305	16012 16007	872 872 A
● TH 5040	5	19	17.500	2,5	10	13306	16013	869 B
● TH 5050 (a)	5	5	2.000	2,5	15	13305	16006	5558/FG 32
● TH 5090 (a)	5	11	15.000	1,5	6	13305	16012	575 A
● TH 5130	5	10	10.000	2,5	10	13305	16030	—
■ TH 5221 $\frac{B}{V}$	2,5	5	10.000	0,4	1,6	13305	16006 16019	3 B 28

B : Culot à broches V : Culot à vis (a) Tube de maintenance. A ne pas utiliser pour un premier équipement.

TH. 5221

TH. 5021

TH. 5050

TH. 5031

TH. 5090

TH. 5130

TH. 5040

